

## P/N S8K201

## **Description**

Thread Size: 1/8", Nut Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: S8K201

Minimum Qty (MOQ): 25 EA

NSN: 5310-00-989-1358

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N S8K201 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.355 Inches Nominal
Key Length:	0.063 Inches Nominal
Head Height:	0.063 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.221 Inches Nominal
Nut Length:	0.562 Inches Nominal
Err Default:	+0.161/+0.201 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Head Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

### **How to Order**

Order this rivnut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/58K201</a> and selecting the quantity you want then