

Description

Fastener Length: 5/8", Thread: 8-32, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	S90938208A
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-133-3630
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N S9093-82-08A Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.553 Inches Minimum And 0.635 Inches Maximum
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Double Hexagon W/ Hole
Head Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Width Between Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum And 0.040 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5732 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/S9093-82-08A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.