

# P/N S9420H3-26

Military-Fasteners.com

#### Description

Fastener Length: 1-5/8", Hole Diameter: 1/32", Thread: 10-24, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	S9420H326
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-005-8592
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N S9420H3-26 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Nominal
Fastener Length:	1.610 Inches Minimum And 1.640 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5735 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unjc

### How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/S9420H3-26</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.