

**Description**

Fastener Length: 1-5/8", Hole Diameter: 1/32", Thread: 10-24, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	S9420H326
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-005-8592
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N S9420H3-26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.625 Inches Nominal
<b>Fastener Length:</b>	1.610 Inches Minimum And 1.640 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.360 Inches Minimum And 0.374 Inches Maximum
<b>Head Height:</b>	0.115 Inches Minimum And 0.125 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Nominal
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/S9420H3-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.