

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	SB45
Minimum Qty (MOQ):	250 EA
NSN:	5320-00-971-7871
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N SB4-5 Specifications

Fastener Length:	0.409 Inches Minimum And 0.439 Inches Maximum
Head Style:	Oval/truss
Head Height:	0.030 Inches Minimum And 0.040 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	280 Single Pounds Per Square Inch
Heat Treatment:	As Fabricated Overall
Material:	Steel Comp 1006 Body Or Steel Comp 1008 Body Or Steel Comp 1009 Body Or Steel Comp 1010 Body
Material:	Steel Comp 1030 Mandrel Or Steel Comp 1033 Mandrel Or Steel Comp 1034 Mandrel Or Steel Comp 1035 Mandrel Or Steel Comp 1536 Mandrel Or Steel Comp 1037 Mandrel Or Steel Comp 1038 Mandrel Or Steel Comp 1039 Mandrel Or Steel Comp 1040 Mandrel Or Steel Comp 1541 Mandrel Or Steel Comp 1042 Mandrel Or Steel Comp 1043 Mandrel Or Steel Comp 1044 Mandrel Or Steel Comp 1045 Mandrel Or Steel Comp 1046 Mandrel Or Steel Comp 1548 Mandrel Or Steel Comp 1049 Mandrel Or Steel Comp 1050 Mandrel Or Steel Comp 1551 Mandrel Or Steel Comp 1552 Mandrel Or Steel Comp 1053 Mandrel Or Steel Comp 1055 Mandrel Or Steel Comp 1059 Mandrel Or Steel Comp 1060 Mandrel
Surface Treatment:	Zinc Body And Chromate Body Or Cadmium Body Or Cadmium Body And Chromate Body Or Cadmium Body And Phosphate Body Or Phosphate Zinc Body
Surface Treatment:	Zinc Mandrel And Chromate Mandrel Or Cadmium Mandrel Or Cadmium Mandrel And Chromate Mandrel Or Cadmium Mandrel And Phosphate Mandrel Or Phosphate Zinc Mandrel
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec 1st Treatment Response Body Or Qq-p-416 Fed Spec 2nd Treatment Response Body Or Qq-p-416 Mil Spec 1st Treatment Response Body Or Qq-p-416 Fed Spec 4th Treatment Response Body Or Mil-p-16232,ty Z,cl 2 Or 4 Mil Spec 5th Treatment Response Body
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec 1st Treatment Response Mandrel Or Qq-p-416 Fed Spec 2nd Treatment Response Mandrel Or Qq-p-416 Mil Spec 1st Treatment Response Mandrel Or Qq-p-416 Fed Spec 4th Treatment Response Mandrel Or Mil-p-16232 Ty Z,cl 2 Or 4 Mil Spec 5th Treatment Response Mandrel

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/SB4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.