

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	SB62
Minimum Qty (MOQ):	500 EA
NSN:	5320-00-850-3247
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N SB6-2 Specifications

<b>Fastener Length:</b>	0.277 Inches Nominal
<b>Head Style:</b>	Oval/truss
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	580 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 1010 Sleeve Or Steel Comp 1006 Sleeve
<b>Material:</b>	Steel Comp 1010 Stem Or Steel Comp 1006 Stem
<b>Material Document And Classification:</b>	Sae Assn Std 1st Material Response Stem Or D66 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Sae Assn Std 1st Material Response Sleeve Or D66 Assn Std 2nd Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Cadmium Sleeve And Phosphate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem Or Cadmium Stem And Chromate Stem Or Cadmium Stem And Phosphate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec All Treatment Responses Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec All Treatment Responses Stem

## How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/SB6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.