

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	SB62
Minimum Qty (MOQ):	500 EA
NSN:	5320-00-850-3247
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N SB6-2 Specifications

Fastener Length:	0.277 Inches Nominal
Head Style:	Oval/truss
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	580 Single Pounds Per Square Inch
Material:	Steel Comp 1010 Sleeve Or Steel Comp 1006 Sleeve
Material:	Steel Comp 1010 Stem Or Steel Comp 1006 Stem
Material Document And Classification:	Sae Assn Std 1st Material Response Stem Or D66 Assn Std 2nd Material Response Stem
Material Document And Classification:	Sae Assn Std 1st Material Response Sleeve Or D66 Assn Std 2nd Material Response Sleeve
Surface Treatment:	Cadmium Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Cadmium Sleeve And Phosphate Sleeve
Surface Treatment:	Cadmium Stem Or Cadmium Stem And Chromate Stem Or Cadmium Stem And Phosphate Stem
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec All Treatment Responses Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec All Treatment Responses Stem

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/SB6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.