

Description

Fastener Length: 1-3/16", Thread: 1/4-28, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	SC1752411P
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-445-3020
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N SC1752-4-11P Specifications

Thread Class:	3a
Thread Length:	0.363 Inches Nominal
Fastener Length:	1.167 Inches Minimum And 1.197 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.466 Inches Minimum And 0.518 Inches Maximum
Internal Drive Style:	Torque-set Ribbed
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/SC1752-4-11P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.