



Military-Fasteners.com

P/N SC5049-3-36

Description

Fastener Length: 2-3/8", Thread: 10-32, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	SC5049336
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-357-2405
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N SC5049-3-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	2.290 Inches Minimum And 2.380 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/SC5049-3-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.