

Description

Fastener Length: 3/8", Pop Rivet, SD34 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | SD34BS |
| Minimum Qty (MOQ): | 250 |
| NSN: | 5320-00-469-4137 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N SD34BS Specifications

| | |
|---|---|
| Fastener Length: | 0.327 Inches Minimum And 0.357 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.022 Inches Minimum And 0.032 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.126 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 165 Single Pounds Per Square Inch |
| Material: | Steel Comp 1006 Body Or Steel Comp 1010 Body |
| Material: | Steel Comp 1070 Mandrel Or Steel Comp 1060 Mandrel |
| Material Document And Classification: | 66 Fed Std All Material Responses Body |
| Surface Treatment: | Zinc Sleeve And Chromate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Cadmium Sleeve And Phosphate Sleeve Or Phosphate Zinc Sleeve |
| Surface Treatment Document And Classification: | Qq-z-325,ty 2,cl 3 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416 Fed Spec 2nd Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/SD34BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.