

Description

Fastener Length: 3/8", Pop Rivet, SD34 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	SD34BS
Minimum Qty (MOQ):	250
NSN:	5320-00-469-4137
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N SD34BS Specifications

Fastener Length:	0.327 Inches Minimum And 0.357 Inches Maximum
Head Style:	Universal
Head Height:	0.022 Inches Minimum And 0.032 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.178 Inches Minimum And 0.198 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.126 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	165 Single Pounds Per Square Inch
Material:	Steel Comp 1006 Body Or Steel Comp 1010 Body
Material:	Steel Comp 1070 Mandrel Or Steel Comp 1060 Mandrel
Material Document And Classification:	66 Fed Std All Material Responses Body
Surface Treatment:	Zinc Sleeve And Chromate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Cadmium Sleeve And Phosphate Sleeve Or Phosphate Zinc Sleeve
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416 Fed Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/SD34BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.