

**Description**

Fastener Length: 3/8", Pop Rivet, SD34 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	SD34BS
Minimum Qty (MOQ):	250
NSN:	5320-00-469-4137
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N SD34BS Specifications

<b>Fastener Length:</b>	0.327 Inches Minimum And 0.357 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.022 Inches Minimum And 0.032 Inches Maximum
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.126 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	165 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 1006 Body Or Steel Comp 1010 Body
<b>Material:</b>	Steel Comp 1070 Mandrel Or Steel Comp 1060 Mandrel
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Body
<b>Surface Treatment:</b>	Zinc Sleeve And Chromate Sleeve Or Cadmium Sleeve And Chromate Sleeve Or Cadmium Sleeve And Phosphate Sleeve Or Phosphate Zinc Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-z-325,ty 2,cl 3 Fed Spec 1st Treatment Response Sleeve Or Qq-p-416 Fed Spec 2nd Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/SD34BS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.