

# P/N SFSW8C10DL01BK

## **Description**

Fastener Length: 5/8", Thread: 8-32, Thread Length: 5/8", SFSW8 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: SFSW8C10DL01BK

Minimum Qty (MOQ): 25

NSN: 5305-00-917-6341

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N SFSW8C10DL01BK Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Dichromate
Special Features:	Furnished W/one Nylon Washer; Painted Black Color No. 37039 Per Fed Std 595
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/SFSW8C10DL01BK">https://military-fasteners.com/screws/machine+screws/SFSW8C10DL01BK</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.