

Description

Thread Size: 1/8", SL213 series nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[13080001-4-3](#)

| | |
|-------------------------|---|
| SKU / Model: | SL213081 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-062-3315 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N SL213-08-1 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Overall Width: | 0.437 Inches Maximum |
| Nut Style: | Floating |
| Distance From Base To Center Of Aperture: | 0.570 Inches Maximum |
| Panel Thickness: | 0.190 Inches Maximum |
| Temp Rating: | -65.0 Deg Fahrenheit Minimum And 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unc |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this clip-on nut from our inventory online by visiting https://military-fasteners.com/nuts/clip_on+nuts/SL213-08-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.