

**Description**

Thread Size: 1/4", Nut Length: 1/2", rivnut

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	SS10K80
Minimum Qty (MOQ):	20
NSN:	5310-01-047-9457
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N SS10K80 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.391 Inches Minimum And 0.421 Inches Maximum
<b>Key Length:</b>	0.061 Inches Maximum
<b>Head Height:</b>	0.038 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.246 Inches Minimum And 0.250 Inches Maximum
<b>Nut Length:</b>	0.516 Inches Minimum And 0.546 Inches Maximum
<b>Err Default:</b>	+0.010/+0.080 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Steel Comp 430 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/SS10K80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.