

## P/N SSD44BS

### **Description**

Fastener Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: SSD44BS

Minimum Qty (MOQ): 335 EA

NSN: 5320-00-155-5250

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N SSD44BS Specifications**

Fastener Length:	0.357 Inches Nominal
Head Style:	Universal
Head Height:	0.035 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	550 Single Pounds Per Square Inch
Material:	Steel Comp 305 Sleeve
Material:	Steel Stem
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Sleeve

# **How to Order**

Order this pop rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/SSD44BS">https://military-fasteners.com/rivets/blind+rivets/SSD44BS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/SSD44BS">https://military-fasteners.com/rivets/blind+rivets/SSD44BS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/SSD44BS">https://military-fasteners.com/rivets/blind+rivets/SSD44BS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/SSD44BS">https://military-fasteners.com/rivets/blind+rivets/SSD44BS</a> and selecting the quantity you want then click "add to cart".