

**Description**

Fastener Length: 7/8", Thread: 10-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | ST3M430V37AS                         |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-00-283-4582                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N ST3M430V3-7AS Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.380 Inches Minimum And 0.447 Inches Maximum   |
| <b>Fastener Length:</b>                      | 0.828 Inches Minimum And 0.875 Inches Maximum   |
| <b>Head Style:</b>                           | Flat Countersunk Undercut   |
| <b>Head Diameter:</b>                        | 0.376 Inches Minimum And 0.381 Inches Maximum   |
| <b>Head Height:</b>                          | 0.044 Inches Minimum  |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum   |
| <b>Internal Drive Style:</b>                 | High-torque   |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches  |
| <b>Grip Length:</b>                          | 0.428 Inches Minimum And 0.448 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Countersink Angle:</b>                    | 99.5 Degrees Minimum And 100.5 Degrees Maximum  |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads  |
| <b>Special Features:</b>                     | Furnished With One O-ring Seal  |
| <b>Material:</b>                             | Titanium Alloy Overall  |
| <b>Material Document And Classification:</b> | Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V3-7AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.