

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M430V38AS
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-283-4583
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N ST3M430V3-8AS Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.447 Inches Maximum
Fastener Length:	0.890 Inches Minimum And 0.937 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.376 Inches Minimum And 0.381 Inches Maximum
Head Height:	0.044 Inches Minimum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Furnished With One O-ring Seal
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V3-8AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.