



Military-Fasteners.com

P/N ST3M430V3-8AS

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M430V38AS
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-283-4583
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

## P/N ST3M430V3-8AS Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.380 Inches Minimum And 0.447 Inches Maximum
<b>Fastener Length:</b>	0.890 Inches Minimum And 0.937 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.376 Inches Minimum And 0.381 Inches Maximum
<b>Head Height:</b>	0.044 Inches Minimum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Special Features:</b>	Furnished With One O-ring Seal
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V3-8AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.