

## Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | ST3M430V410AS                        |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-00-283-7456                     |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



# P/N ST3M430V4-10AS Specifications

|                                       |   |
|---------------------------------------|---|
| Thread Class:                         | 3a  |
| Thread Direction:                     | Right-hand  |
| Thread Length:                        | 0.443 Inches Minimum And 0.510 Inches Maximum   |
| Fastener Length:                      | 1.078 Inches Minimum And 1.125 Inches Maximum   |
| Head Style:                           | Flat Countersunk Undercut   |
| Head Diameter:                        | 0.502 Inches Minimum And 0.507 Inches Maximum   |
| Head Height:                          | 0.071 Inches Minimum And 0.073 Inches Maximum   |
| Grip Diameter:                        | 0.2490 Inches Minimum And 0.2495 Inches Maximum   |
| Internal Drive Style:                 | High-torque   |
| Nominal Thread Diameter:              | 0.250 Inches  |
| Grip Length:                          | 0.615 Inches Minimum And 0.635 Inches Maximum   |
| Thread Quantity Per Inch:             | 28  |
| Countersink Angle:                    | 99.5 Degrees Minimum And 100.5 Degrees Maximum  |
| Surface Finish:                       | 32.0 Microinches Grip   |
| Surface Finish:                       | 32.0 Microinches Threads  |
| Special Features:                     | Furnished With One O-ring Seal  |
| Material:                             | Titanium Alloy Overall  |
| Material Document And Classification: | Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall |
| Thread Series Designator:             | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-10AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.