



Military-Fasteners.com

P/N ST3M430V4-10ASM

Description

Fastener Length: 1-1/8", Thread: 1/4-29, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M430V410ASM
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-347-4022
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M430V4-10ASM Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	1.078 Inches Minimum And 1.125 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.5018 Inches Minimum And 0.5066 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.108 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Features Provided:	O Ring And Dry Film Lubricant And Cetyl Alcohol Lubricant
Thread Quantity Per Inch:	29
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Special Features:	Fluorsilicon Rubber O-ring,per Mil-r-25988 Ty1,cl 1,grade 70 Lubricants Applied On Shank And Threads
Material:	Titanium Alloy Uns R56400 Fastener
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Fastener
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-10ASM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.