

Description

Fastener Length: 1-3/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | ST3M430V411AS |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-103-5732 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



P/N ST3M430V4-11AS Specifications

| | |
|----------------------------------------------|--------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.442 Inches Minimum And 0.509 Inches Maximum |
| Fastener Length: | 1.140 Inches Minimum And 1.187 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.5066 Inches Maximum |
| Head Height: | 0.071 Inches Minimum And 0.073 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | High-torque |
| End Item Identification: | Eagle F-15, F/a-18 Hornet, Harrier |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Furnished With 1 O-ring |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Nas621 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-11AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.