

**Description**

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M430V413ASM
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-312-0701
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N ST3M430V4-13ASM Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.443 Inches Minimum And 0.510 Inches Maximum
<b>Fastener Length:</b>	1.265 Inches Minimum And 1.312 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.4750 Inches Minimum And 0.5066 Inches Maximum
<b>Head Height:</b>	0.0713 Inches Minimum And 0.0733 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.802 Inches Minimum And 0.822 Inches Maximum
<b>Features Provided:</b>	Dry Film Lubricant And O Ring And Cetyl Alcohol Lubricant
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Special Features:</b>	Fluorsilicone Rubber O-ring,per Mil-r-25988 Ty1,cl 1,gr 70; Lubricants Applied On Shank And Threads
<b>Material:</b>	Titanium Alloy Uns R56400 Fastener
<b>Material Document And Classification:</b>	Ams 4967 Assn Std Single Material Response Fastener
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-13ASM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.