



Military-Fasteners.com

P/N ST3M430V4-13ASM

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M430V413ASM
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-312-0701
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N ST3M430V4-13ASM Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.443 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	1.265 Inches Minimum And 1.312 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.4750 Inches Minimum And 0.5066 Inches Maximum
Head Height:	0.0713 Inches Minimum And 0.0733 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Features Provided:	Dry Film Lubricant And O Ring And Cetyl Alcohol Lubricant
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Fluorsilicone Rubber O-ring,per Mil-r-25988 Ty1,cl 1,gr 70; Lubricants Applied On Shank And Threads
Material:	Titanium Alloy Uns R56400 Fastener
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Fastener
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-13ASM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.