

**Description**

Fastener Length: 1-7/16", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | ST3M430V415AS                        |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-01-131-8168                     |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



\* See page 2 for technical characteristics

## P/N ST3M430V4-15AS Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.442 Inches Minimum And 0.509 Inches Maximum     |
| <b>Fastener Length:</b>                      | 1.390 Inches Minimum And 1.437 Inches Maximum     |
| <b>Head Style:</b>                           | Flat Countersunk Undercut                         |
| <b>Head Diameter:</b>                        | 0.502 Inches Minimum And 0.507 Inches Maximum     |
| <b>Head Height:</b>                          | 0.071 Inches Minimum And 0.073 Inches Maximum     |
| <b>Grip Diameter:</b>                        | 0.2490 Inches Minimum And 0.2495 Inches Maximum   |
| <b>Internal Drive Style:</b>                 | High-torque                                       |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches                                      |
| <b>Grip Length:</b>                          | 0.928 Inches Minimum And 0.948 Inches Maximum     |
| <b>Thread Quantity Per Inch:</b>             | 28  |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal                             |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                             |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                          |
| <b>Special Features:</b>                     | Furnish With One O Ring                           |
| <b>Material:</b>                             | Titanium Alloy Overall                            |
| <b>Material Document And Classification:</b> | Nas 621 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-15AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.