

**Description**

Fastener Length: 13/16", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M430V45ASM
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-538-4369
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

## P/N ST3M430V4-5ASM Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.443 Inches Minimum And 0.510 Inches Maximum
<b>Fastener Length:</b>	0.765 Inches Minimum And 0.812 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.502 Inches Minimum And 0.507 Inches Maximum
<b>Head Height:</b>	0.071 Inches Minimum And 0.073 Inches Maximum
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Special Features:</b>	Furnished With One O-ring Seal. Shank And Threads Have Dry Film Lubricant Applied, Reply Code Lbg000 Not Listed This Fiig
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-5ASM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.