

Description

Fastener Length: 15/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M430V47AS
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-283-4587
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N ST3M430V4-7AS Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.442 Inches Minimum And 0.509 Inches Maximum
Fastener Length:	0.890 Inches Minimum And 0.937 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.502 Inches Minimum And 0.507 Inches Maximum
Head Height:	0.071 Inches Minimum And 0.073 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	Aircraft, Eagle F-15;aircraft, Hornet F/a-18;aircraft, Harrier Av-8b
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Furnished With One O-ring Seal
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-7AS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.