

**Description**

Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | ST3M430V49ASM                             |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-01-344-5533                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N ST3M430V4-9ASM Specifications

|                                              |                                                   |
|----------------------------------------------|---------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                |
| <b>Thread Direction:</b>                     | Right-hand                                        |
| <b>Thread Length:</b>                        | 0.469 Inches Nominal                              |
| <b>Fastener Length:</b>                      | 1.015 Inches Minimum And 1.062 Inches Maximum     |
| <b>Head Style:</b>                           | Fillister Countersunk                             |
| <b>Head Diameter:</b>                        | 0.5018 Inches Minimum And 0.5066 Inches Maximum   |
| <b>Head Height:</b>                          | 0.051 Inches Minimum And 0.054 Inches Maximum     |
| <b>Grip Diameter:</b>                        | 0.2490 Inches Minimum And 0.2495 Inches Maximum   |
| <b>Internal Drive Style:</b>                 | High-torque                                       |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches                                      |
| <b>Grip Length:</b>                          | 0.552 Inches Minimum And 0.572 Inches Maximum     |
| <b>Features Provided:</b>                    | Dry Film Lubricant And O Ring                     |
| <b>Thread Quantity Per Inch:</b>             | 28                                                |
| <b>Countersink Angle:</b>                    | 99.0 Degrees Minimum And 101.0 Degrees Maximum    |
| <b>Material:</b>                             | Titanium Alloy Uns R56400 Overall                 |
| <b>Material Document And Classification:</b> | Ams4967 Assn Std Single Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf                                              |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V4-9ASM> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.