



Military-Fasteners.com

P/N ST3M430V5-10D

Description

Fastener Length: 1-3/16", Thread: 1/4-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | ST3M430V510D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-324-8493 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N ST3M430V5-10D Specifications

| | |
|---------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.505 Inches Minimum And 0.572 Inches Maximum |
| Fastener Length: | 1.140 Inches Minimum And 1.187 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.628 Inches Minimum And 0.633 Inches Maximum |
| Head Height: | 0.087 Inches Minimum And 0.089 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 100.0 Degrees Minimum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Nas 621,6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M430V5-10D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.