

**Description**

Fastener Length: 17/32", Thread: 10-32, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M4543L2
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-029-8160
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N ST3M454-3L2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.381 Inches Minimum And 0.431 Inches Maximum
<b>Fastener Length:</b>	0.516 Inches Minimum And 0.546 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.376 Inches Minimum And 0.385 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	23-112,mcdonnell Douglas Corp Mfr Ref Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M454-3L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.