

Description

Fastener Length: 17/32", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M4543L2
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-029-8160
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M454-3L2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	0.516 Inches Minimum And 0.546 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.376 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Material Document And Classification:	23-112,mcdonnell Douglas Corp Mfr Ref Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M454-3L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.