

Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M4543L4
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-324-9249
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M454-3L4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	0.641 Inches Minimum And 0.671 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.376 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	Aircraft, Hornet F/a-18 (e/f);aircraft, Eagle F-15;aircraft, Hornet F/a-18;aircraft, Harrier Av-8b;aircraft, B-1b
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Overall
Material Document And Classification:	23-112 Fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M454-3L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.