

P/N ST3M454-3L4

Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: ST3M4543L4

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-324-9249

Schedule B: 7318.15.2091

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N ST3M454-3L4 Specifications

| Thread Class: | 3a |
|---------------------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.381 Inches Minimum And 0.431 Inches Maximum |
| Fastener Length: | 0.641 Inches Minimum And 0.671 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.376 Inches Minimum And 0.385 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | High-torque |
| End Item Identification: | Aircraft, Hornet F/a-18 (e/f);aircraft, Eagle F-15;aircraft, Hornet F/a-18;aircraft, Harrier Av-8b;aircraft, B-1b |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Overall |
| Material Document And Classification: | 23-112 Fscm 76301 Mfr Ref Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/ST3M454-3L4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/ST3M454-3L4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/ST3M454-3L4 and selecting the quantity you want then click "add to cart".