

Description

Fastener Length: 1-5/32", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M4553L121
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-354-4240
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M455-3L12-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	1.141 Inches Minimum And 1.171 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M455-3L12-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.