

**Description**

Fastener Length: 1-13/32", Thread: 10-32, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M4553L161
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-354-4252
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N ST3M455-3L16-1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.381 Inches Minimum And 0.431 Inches Maximum
<b>Fastener Length:</b>	1.391 Inches Minimum And 1.421 Inches Maximum
<b>Head Style:</b>	Oval Countersunk
<b>Head Diameter:</b>	0.297 Inches Minimum And 0.302 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M455-3L16-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.