



Military-Fasteners.com

P/N ST3M455-4L20-1

Description

Fastener Length: 1-47/64", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M4554L201
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-316-8103
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M455-4L20-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.704 Inches Minimum And 1.734 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.389 Inches Minimum And 0.394 Inches Maximum
Head Height:	0.015 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	23-112,fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M455-4L20-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.