

Description

Fastener Length: 1-9/32", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M4556L10M
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-049-8189
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M455-6L10M Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.616 Inches Minimum And 0.666 Inches Maximum
Fastener Length:	1.251 Inches Minimum And 1.281 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.510 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	Aircraft, Eagle F-15
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Dry Film Lubricant P.s. 18021 CI 1
Material:	Steel Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	76301-st3-455 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M455-6L10M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.