

Description

Fastener Length: 1-9/32", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | ST3M4556L10M |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-049-8189 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N ST3M455-6L10M Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.616 Inches Minimum And 0.666 Inches Maximum |
| Fastener Length: | 1.251 Inches Minimum And 1.281 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.510 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3740 Inches Minimum And 0.3745 Inches Maximum |
| Internal Drive Style: | High-torque |
| End Item Identification: | Aircraft, Eagle F-15 |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Dry Film Lubricant P.s. 18021 CI 1 |
| Material: | Steel Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 76301-st3-455 Professional/Industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M455-6L10M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.