

Description

Fastener Length: 1-9/32", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M466V6L101
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-008-6725
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N ST3M466V6L10-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.616 Inches Minimum And 0.666 Inches Maximum
Fastener Length:	1.251 Inches Minimum And 1.281 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.5544 Inches Minimum And 0.5604 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M466V6L10-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.