

Description

Fastener Length: 1-13/64", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M466V6L9M1
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-049-8190
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N ST3M466V6L9M1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.616 Inches Minimum And 0.666 Inches Maximum
Fastener Length:	1.188 Inches Minimum And 1.218 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.554 Inches Minimum And 0.560 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Finish:	32.0 Microinches Top Of Head
Special Features:	Dry Film Lubricant P.s. 18021 Cl 1
Material:	Titanium Alloy Overall
Thread Series Designator:	Unjf
Specification/standard Data:	76301-st3-466 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M466V6L9M1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.