

**Description**

Fastener Length: 1-9/32", Thread: 7/16-20, Thread Length: 43/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M466V7L10M1
Minimum Qty (MOQ):	1
NSN:	5305-01-050-4992
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N ST3M466V7L10M1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.631 Inches Minimum And 0.681 Inches Maximum
<b>Fastener Length:</b>	1.266 Inches Minimum And 1.296 Inches Maximum
<b>Head Style:</b>	Oval Countersunk
<b>Head Diameter:</b>	0.662 Inches Minimum And 0.668 Inches Maximum
<b>Grip Diameter:</b>	0.4365 Inches Minimum And 0.4370 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Surface Finish:</b>	32.0 Microinches Top Of Head
<b>Special Features:</b>	Dry Film Lubricant P.s. 18021 CI 1
<b>Material:</b>	Titanium Alloy Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	76301-st3-466 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M466V7L10M1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.