

Description

Fastener Length: 1-23/64", Thread: 7/16-20, Thread Length: 43/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M466V7L11M1
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-050-4993
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N ST3M466V7L11M1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.631 Inches Minimum And 0.681 Inches Maximum
Fastener Length:	1.329 Inches Minimum And 1.359 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.662 Inches Minimum And 0.668 Inches Maximum
Grip Diameter:	0.4365 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Finish:	32.0 Microinches Top Of Head
Special Features:	Dry Film Lubricant P.s. 18021 CI 1
Material:	Titanium Alloy Overall
Thread Series Designator:	Unjf
Specification/standard Data:	76301-st3-466 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M466V7L11M1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.