



Military-Fasteners.com

P/N ST3M466V7L8-1

Description

Fastener Length: 1-5/32", Thread: 7/16-20, Thread Length: 43/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M466V7L81
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-486-1154
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N ST3M466V7L8-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.631 Inches Minimum And 0.681 Inches Maximum
Fastener Length:	1.141 Inches Minimum And 1.171 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.662 Inches Minimum And 0.668 Inches Maximum
Grip Diameter:	0.4365 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas621,comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M466V7L8-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.