

Description

Fastener Length: 1-13/32", Thread: 1/2-20, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | ST3M466V8L10M1 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-050-3830 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N ST3M466V8L10M1 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.756 Inches Minimum And 0.806 Inches Maximum |
| Fastener Length: | 1.391 Inches Minimum And 1.421 Inches Maximum |
| Head Style: | Oval Countersunk |
| Head Diameter: | 0.747 Inches Minimum And 0.752 Inches Maximum |
| Grip Diameter: | 0.4990 Inches Minimum And 0.4995 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.500 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Special Features: | Dry Film Lubricant P.s. 18021 Cl 1 |
| Material: | Titanium Alloy Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 76301-st3-466 Professional/industrial Association Standard |

How to Order

Order this ht bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M466V8L10M1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.