



Military-Fasteners.com

P/N ST3M466V8L10M1

Description

Fastener Length: 1-13/32", Thread: 1/2-20, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M466V8L10M1
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-050-3830
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N ST3M466V8L10M1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.756 Inches Minimum And 0.806 Inches Maximum
Fastener Length:	1.391 Inches Minimum And 1.421 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.747 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Special Features:	Dry Film Lubricant P.s. 18021 Cl 1
Material:	Titanium Alloy Overall
Thread Series Designator:	Unjf
Specification/standard Data:	76301-st3-466 Professional/Industrial Association Standard

How to Order

Order this ht bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M466V8L10M1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.