

**Description**

Fastener Length: 1-15/64", Thread: 1/2-20, Thread Length: 51/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M466V8L71
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-310-6421
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

# P/N ST3M466V8L7-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.756 Inches Minimum And 0.806 Inches Maximum
Fastener Length:	1.204 Inches Minimum And 1.234 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.747 Inches Minimum And 0.753 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M466V8L7-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.