



Military-Fasteners.com

P/N ST3M505-3-12

Description

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M505312
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-046-0715
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N ST3M505-3-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.3310 Inches Nominal
Fastener Length:	1.0650 Inches Minimum And 1.1220 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.3760 Inches Minimum And 0.3850 Inches Maximum
Shoulder Diameter:	0.3270 Inches Minimum First Shoulder And 0.3272 Inches Maximum First Shoulder
Shoulder Length:	0.0448 Inches Minimum First Shoulder And 0.0474 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.1900 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M505-3-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.