

Description

Fastener Length: 51/64", Thread: 10-32, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M50537
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-045-9641
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M505-3-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.331 Inches Nominal
Fastener Length:	0.753 Inches Minimum And 0.800 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.376 Inches Minimum And 0.385 Inches Maximum
Shoulder Length:	0.0448 Inches Minimum First Shoulder And 0.0474 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
End Item Identification:	Fms - Aircraft, Hornet F/a-18;aircraft, Eagle F-15;aircraft, Hornet F/a-18;aircraft, Harrier Av-8b
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M505-3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.