

Description

Fastener Length: 55/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | ST3M50538 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-049-5732 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N ST3M505-3-8 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.815 Inches Minimum And 0.862 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0806 Inches Maximum |
| Shank Diameter: | 0.2177 Inches Minimum And 0.2182 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.385 Inches Maximum |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 125000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Corrosion Resisting Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M505-3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.