

**Description**

Fastener Length: 1-7/32", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M505413
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-050-9678
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N ST3M505-4-13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.372 Inches Minimum And 0.422 Inches Maximum
<b>Fastener Length:</b>	1.194 Inches Minimum And 1.224 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.497 Inches Minimum And 0.507 Inches Maximum
<b>Shoulder Diameter:</b>	0.2802 Inches Minimum First Shoulder And 0.2807 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.707 Inches Minimum First Shoulder And 0.727 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Special Features:</b>	Internal Hexagon Socket In Threaded End 0.0947 In. Min And 0.0967 In. Max Width Across Flats
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M505-4-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.